



EcoQuip™ 2 EQp

Vapour abrasive blasting

A cleaner and easier way of blasting for more profitable and durable results.

- ▶ **Small and portable** – makes it easy to move on the deck. It can handle both horizontal and vertical surfaces
- ▶ **Atex approved** – can be used on all vessel types (even tankers)
- ▶ **Environmental friendly** – 92% less dust and up to 75% media savings compared to dry blasting. Uses less water than traditional water-based wet blasting, pressure washing or hydro jetting
- ▶ **No health risks** – No risks due to vibrations caused by hand tools
- ▶ **Surface preparation** – perfect feathering which creates a good adhesion of the paint, compatible with almost all grit types



GET A FREE DEMO

EcoQuip™ 2 Eqp

Vapour abrasive blasting



Easy-to-use Controls

- Blast air pressure
- Abrasive meter
- Selector valve for washdown or blast

Abrasive Metering Valve

- Precise control of media
- Lockable set-point

Blast Hose Control Lines

- Pneumatic operation
- Blasts up to 50 meter from machine

Enclosure with Controls

- Blast circuit, water pump and air/water controls

Media Funnel and Pop-Up Seal

- Removable for clean-out access
- Built-in strainer

Quick-Fill Valve

- Speeds up the fill/flush process with garden hose pressure

Blast Hose Connection

- Accepts 1/2" or 1" blast hose

Water Inlet Connection

- Garden hose, siphon or water tank supply options

Flat-free Wheels

- Rugged and durable to get around your job site smoothly

EcoQuip 2 Eqp

Maximum Air Inlet Pressure	10.3 bar (150 psi, 1.03 Mpa)
Operating Temperature	1.6°- 43.3°C (35°-110°F)
Recommended Compressor Size	5.2 m ³ /min (185 cfm)
Abrasive Capacity*	100 kg (220 lbs)
Dry Weight	100 kg (220 lbs)
Wet Weight*	227 kg (500 lbs)
Pressure Pot Volume	55L
Air Inlet Connection**	Universal, Chicago-style claw
Blast Connection***	2 Lug Claw Coupler
Water Inlet Connection****	3/4 in garden hose connection

* Abrasive Capacity and wet weight using 80 grit garnet.

** A 3/4" Male NPT connects to the universal claw out of the system.

*** A 1.25" NPSM connects to the 2 lug claw coupler out of the system.

**** Siphon kit is included with an available 3/4" NPT adapter kit.

GET A FREE DEMO